

David White®

ML-600N and ML-450N Visible Split-Beam Manual Level Lasers

- **Compact. Easy to use.**
Easy on your budget
- **One-button operation**
gives you all of the speed, accuracy and practical features you need for one-man leveling operations.
- **Rugged and Durable** –
Built with unbeatable David White quality to ensure years of dependable operation.



ML-600N
Features Auto Out-of-level Shut-off and
Remote Control Capability.

**The brightest idea
in low cost laser
technology.**

AutoLaser® ML-Series Rotary Lasers



360° rotating beacon, split-beam with "point and shoot" sweep

Leveling vials are enclosed for protection and shielded for use in bright sunlight

Easy access rear battery door

One switch controls On/Off, sweep mode, and rotation speed

Easy 2-screw leveling base

Remote control sensor (ML-600N Only)

Attaches to any 5/8 x 11 JIS flat head tripod, or lay unit on its built-in trivet for vertical applications

Product Specifications

Beam Type: Visible 635 nm Laser Diode
2.5 mw maximum (Class IIIa)

Operating Range: 200 feet (60M) diameter interior visible range with reflective target*; 800 feet (244M) diameter range with LD-12N detector

Level Vial Sensitivity: 5 minutes

Plumb Vial Sensitivity: 10 minutes

Accuracy: ± 1/4" @ 100 feet (± 6mm @ 30M)

Battery life: 4 "C" Cell Alkaline batteries. Fully charged, to 60 hours continuous operation

Rotation Modes: Slow, fast, and spot mode

Construction: Durable plastic housing

Weight (Laser Only): 3.6 lbs. (1.6 kg)

Mounting: 5/8 x 11 JIS flat-head tripod

ALL SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.



Government regulations require the use of these warnings.

Laser System Components

47-4720N **ML-450N**, four "C" cell batteries, owner's manual, electronic laser detector, wall/ceiling mount, grid target with magnetic base, red laser glasses, aluminum tripod, aluminum leveling rod, and carrying case.

47-4810N **ML-600N**, four "C" cell batteries, owner's manual, electronic laser detector, wall/ceiling mount, grid target with magnetic base, red laser glasses, aluminum tripod, aluminum leveling rod, and carrying case.

Accessories

47-5443N Remote Control for ML-600N *Only*

47-5404N LD-12N Detector with Battery and Rod Clamp

47-5301N Rod Detector Bracket for LD-12N

47-5303N Wall/Ceiling Mount, Adjustable

47-5310N Grid Target with Magnetic Base

47-GLASSES Red Laser Glasses

David White®

P.O. Box 359
Watseka, IL 60970, U.S.A.
Phone: 815-432-5237, 800-435-1859
FAX: 800-913-0049
URL: www.davidwhite.com

Available at your local David White dealer.