



Contractors' #1 Choice

5+ Years Proven Performance

2 Year "No Excuses" Warranty SM



LIGHTNING™

The Benchmark of Laser Detector Performance



Apache builds the toughest and most accurate laser detectors in the world.

Field Proven Performance



- Patented detection technology provides stable and accurate grade information over the entire jobsite.
- The world's loudest - 110 decibels loud. Designed to be heard on noisy jobsites.
- Dual displays provide instant visual grade information, battery status, and current detector settings.
- Error free marking - notch is located next to receiving photocells for accurate marking.

Solid, Tough, and Versatile

- 100% waterproof and dustproof, including the battery compartment. Dunk it, scrub it, hose it off.
- 2-Year "No Excuses" Warranty. Any problem? Get it back to us in one piece and we will fix it or replace it. Period. **No Excuses.**
- 4 accuracy settings, 3 volume levels, LCD backlighting.
- Works with all rotating lasers - including yours.



The Best Clamp

- Patented reversible mounting jaw on clamp grips like a vise on all sizes and shapes of rods - square, round, or oval.
- No special adapters required to work with your rod.
- Won't slip, bend, flex, or break.



Optional Remote Display puts an LCD at eye level if the detector is above or below the work area.



Optional Bubble Vial attaches to clamp to assist in vertical rod alignment.

Specifications

Working Range:	Up to 2000 ft. (600 m) radius		
Detection Accuracy:	Zero:	±0"	(±0.00mm)
	Fine:	±1/32"	(±1.00mm)
	Medium:	±1/16"	(±2.00mm)
	Coarse:	±1/8"	(±3.00mm)
Reception Angle:	±45°		
Detection Height:	2" (50mm)		
Environment:	Waterproof, Dustproof to IP67		
Beeper Volumes:	High: 105-110 dBA / Low: 70-75 dBA / Off		
LCD Backlighting:	Yes, front and rear		
Remote Display Outputs:	Yes, 2 contacts		
Power Supply:	2 x 1.5 V "AA" batteries		
Battery Life:	> 50 hours continuous usage > 150 hours normal usage		
Automatic Shut Off:	30 minutes		
Operating Temperature:	-4° F to +120° F (-20°C to +50°C)		
Weight (with batteries):	10 oz. / 16 oz. with Clamp (0.28 kg / 0.45 kg)		
Dimensions (LxWxD):	6.4 x 2.9 x 1.0" (163 x 74 x 26mm)		

* Features and specifications subject to improvement without notice.



Ask about our detector Trade-In Program



Apache also manufactures the full line of BULLSEYE Grade Display Systems.



7415 Chambersburg Road
Dayton, Ohio 45424 USA
Phone: 937-236-8001
Toll Free: 888-272-2433
Fax: 937-236-8012
www.apache-laser.com



MADE IN USA

© Apache Technologies, Inc. 5/02 Reorder P/N LD44R2